

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/057185 A1

(51) International Patent Classification⁷: F04B 35/04, 39/02

(74) Agent: PARK, Jang-Won; Jewoo Bldg. 5th Floor, 200, Nonhyun-Dong, Gangnam-Gu, Seoul 135-010 (KR).

(21) International Application Number:
PCT/KR2003/001372

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 10 July 2003 (10.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2002-0081899
20 December 2002 (20.12.2002) KR

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-Dong, Youngdungpo-Gu, Seoul 150-010 (KR).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): KWON, Gi-Bong [KR/KR]; Daedong Apt. 608-1301, Seokbongmaeul, Sammoon-Li, Jangyu-Myeon, Gimhae, Gyungsangnam-Do 621-831 (KR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: REFRIGERATING SYSTEM HAVING RECIPROCATING COMPRESSOR



(57) Abstract: A refrigerating system includes: an evaporator (2) for performing a cooling operation as a refrigerant is evaporated; a compressor (4) for compressing the refrigerant discharged from the evaporator as a mover is reciprocally moved; a condenser (6) for changing the refrigerant compressed in the reciprocating compressor to a liquid refrigerant; and a capillary tube (8) for decompressing the refrigerant discharged from the condenser and transferring it to the evaporator. The refrigerant is an HFC refrigerant, hydrogenated carbon fluoride comprising hydrogen, fluorine and carbon and the lubricant is an ester-based lubricant, a sort of synthetic fluid, so that a lubricating performance and a performance of the refrigerating system can be improved.

WO 2004/057185 A1